



Elastomer Bellow Mechanical Seals

LY560A

- **Operational Conditions:**
 Temperature: -20℃ to +120℃
 Pressure: ≤ 1.0MPa
 Speed: ≤ 15m/s
- **Materials:**
 Stationary Ring: V1,Q2,Q1,U2
 Rotary Ring: B,A,Q1,Q2
 Secondary Seal: P,E,V
 Spring and Metal Parts: F,G
- **Applications:** Clean water, sewage water,
 Oil and other moderately corrosive fluids.



规格/Size (公制/Metric)	d	D3	D1	L2	L1
560A-8	8	18.2	21	7	11.2
560A-9	9	18.2	24	7	16.2
560A-10	10	20.6	24	7	16.2
560A-11	11	20.6	24	7	16.2
560A-12	12	21.8	26	7	17.2
560A-13	13	21.8	26	7	17.2
560A-14	14	26.4	28	7	18.2
560A-15	15	26.4	28	7	18.2
560A-16	16	26.4	32	8	19.2
560A-17	17	29.5	32	8	19.2
560A-18	18	29.5	35	8	19.2
560A-19	19	29.5	35	8	19.2
560A-20	20	31.6	38	8	20.2
560A-22	22	33.6	40	8	20.2
560A-25	25	39.6	44	9	20.2
560A-28	28	45.0	46	9	21.2
560A-30	30	46.6	50	9	22.2
560A-32	32	46.6	54	9	24.2
560A-35	35	50.8	58	10	26.2
560A-38	38	54.3	60	10	27.2
560A-40	40	57.3	64	10	28.2
560A-45	45	61.3	66	10	30.2
560A-50	50	67.8	72	10	32.2

规格/Size (英制/Inch)	d	D3	D1	L2	L1
560A-3/8	9.52	23.5	22.22	6.4	22.2
560A-1/2	12.7	26.0	25.4	6.4	22.2
560A-5/8	15.8	30.0	31.75	8.7	23.8
560A-3/4	19.1	32.5	34.92	8.7	23.8
560A-7/8	22.2	37.5	38.10	8.7	25.4
560A-1	25.4	44.0	41.27	9.5	27.0
560A-1-1/8	28.6	48.0	44.45	9.5	28.6
560A-1-1/4	31.7	50.0	47.62	9.5	28.6
560A-1-3/8	34.9	54.5	50.80	9.5	30.2
560A-1-1/2	38.1	58.5	53.97	9.5	30.2
560A-1-5/8	41.2	64.0	60.32	11.1	36.5
560A-1-3/4	44.4	67.0	63.50	11.1	36.5
560A-1-7/8	47.6	71.0	66.67	11.1	39.7
560A-2	50.8	73.5	69.85	11.1	39.7