

Elastomer Bellow Mechanical Seals

LYFBD

● Operational Conditions:

Temperature: -20℃ to +120℃

Pressure: ≤ 1.4MPa

Speed: ≤ 15m/s

● Materials:



Stationary Ring: V1,Q2,Q1,U2,U1

Rotary Ring: B,A,Q1,Q2,U1,U2

Secondary Seal: P,E,V

Spring and Metal Parts: F,G

● Applications: Clean water, sewage water, Oil and other moderately corrosive fluids.



规格/Size (公制/Metric)	d	D3	D1	L1	L2
16	16	34.0	30	25	8
18	18	36.8	32	25	8
20	20	38.8	34	25	8
22	22	41.5	36	25	8
25	25	44.8	39	26	8
28	28	48.5	43	26	8
30	30	52.0	48	26	8
35	35	57.0	53	30	10
40	40	67.0	58	34	10
45	45	73.0	63	36	10
50	50	79.0	68	41	10
55	55	84.0	73	41	12
60	60	90.0	79	41	12
65	65	98.5	86	49	12
70	70	103.5	91	52	12
75	75	110.5	96	52	12
80	80	120.0	105	56	14
85	85	125.0	110	56	14
90	90	132.0	115	56	14
95	95	137.0	120	56	14
100	100	144.0	125	62	14
110	110	157.0	135	62	16
120	120	169.5	145	72	16