



Elastomer Bellow Mechanical Seals

LY60/65

- **Operational Conditions:**
 Temperature: -20℃ to +120℃
 Pressure: ≤ 0.5MPa
 Speed: ≤ 10m/s
- **Materials:**
 Stationary Ring: Q1,V1
 Rotary Ring: B5,B,Q2
 Secondary Seal: V,E,P
 Spring and Metal Parts: F,G
- **Applications:** Clean water, sewage water,
 Oil and other moderately corrosive fluids.



规格/Size (英制/Inch)	d	D3	D1	L1	L2
LY60/0.375	9.5	24.00	22.2	16.00	6.20
LY60/0.500	12.7	27.00	25.4	16.60	6.20
LY60/0.625	15.8	31.00	31.8	18.70	10.31
LY60/0.750	19.0	34.20	34.9	18.70	10.31
LY60/1.000	25.4	43.00	41.3	20.60	11.10
LY65/0.375	9.5	27.00	25.4	16.60	7.90
LY65/0.500	12.7	27.00	25.4	16.60	7.90
LY65/0.625	15.8	31.00	31.7	18.20	10.30
LY65/0.750	19.1	34.20	34.9	18.20	10.30
LY65/1.750	63.5	51.59	61.0	33.34	10.32