Elastomer Bellow Mechanical Seals

LY150

● Operational Conditions: Temperature: -40 °C to+150 °C Pressure: ≤ 1.2MPa Speed: ≤15m/s

 Materials: Stationary Ring: Q2,B,V1 Rotary Ring: Q2,B,U2 Secondary Seal: P,E,V

Spring and Metal Parts: F,G

Applications: Clean water, sewage water,
Oil and other moderately corrosive fluids.





规格/Size (公制/Metric)	D1				L2	
10	24.60	16.00	20.0	25.40	8.74	7.47
12	27.79	19.05	22.0	25.40	8.74	7.47
13	27.79	19.05	22.0	25.40	8.74	7.47
14	30.95	22.23	24.0	25.40	10.32	8.97
15	30.95	22.23	25.0	25.40	10.32	8.97
16	30.95	22.23	26.0	25.40	10.32	8.97
18	34.15	25.40	32.0	25.40	10.32	8.97
19	34,15	25.40	32.0	25.40	10.32	8.97
20	35.70	26.99	34.0	25.40	10.32	8.97
22	37.30	28.58	36.0	25.40	10.32	8.97
24	40.50	31.75	38.0	25.40	10.32	8.97
25	40.50	31.75	39.0	25.40	10.32	8.97
28	47.63	35.72	42.0	33.34	11.99	10.46
30	50.80	38.89	44.0	33.34	11.99	10.46
32	50.80	38.89	46.0	33.34	11.99	10.46
33	53,98	42.07	47.0	33.34	11.99	10.46
34	53.98	72.07	49.0	33.34	11.99	10.46
35	53.98	42.07	49.0	33.34	11.99	10.46
38	57.15	45.24	54.0	33.34	11.99	10.46
40	60.35	48.82	56.0	33.34	11.99	10.46
42	63.50	51.59	59.0	40.48	11.99	10.46
43	63.50	51.59	59.0	40.48	11,99	10.46
44	63.50	51.59	61.0	40.48	11.99	10.46
45	63.50	51.59	61.0	40.48	11.99	10.46
48	66.70	54.75	64.0	40.48	11.99	10.46
50	69.85	58.00	66.0	40.48	13.50	10,46
53	73.05	62.00	69.0	41.00	13.50	11.96
55	76.20	65.00	71.0	41.00	13.50	11.96
58	79.40	68.00	78.0	41.00	13.50	11.96
60	79.40	68.00	80.0	41.00	13.50	11.96
63	82.55	71.20	83.0	41.00	13.50	11,96
65	92.10	78.35	85.0	49.00	15.90	14.50
70	95.25	81,10	90.0	49.00	15.90	14.50
73	98.45	84.50	96.0	49.00	15.90	14.50
75	101.65	88.10	99.0	49.00	15.90	14.50
80	114.30	97.00	104.0	56.00	20.00	18.50
85	117.50	100.00	109.0	56.00	20.00	18.50
90	123.85	107.00	114.0	59.00	20.00	18.50
95	127.00	110.00	119.0	59.00	20.00	18.50
100	133.35	116.00	124.0	62.00	20.00	18,50