


Metal Bellow Mechanical Seals

LY688

- **Operational Conditions:**
 Temperature: -75℃ to +400℃
 Pressure: ≤ 2.0MPa (Single)
 Speed: ≤ 23m/s
- **Materials:**
 Stationary Ring: U2, Q2
 Rotary Ring: B, Q2, U2
 Secondary Seal: Graphite
 Bellows: T6,
 Spring and Metal parts: F, G
- **Applications:** Oil, light hydrocarbon, aromatic Hydrocarbon, organic solvents, weak acids, ammonia etc.



规格/Size (公制/Metric)	d	D3	L1
25.40	25.40	41.28	38.95
28.58	28.58	44.45	39.87
31.75	31.75	47.63	40.66
34.93	34.93	50.80	40.66
38.10	38.10	53.98	40.66
41.28	41.28	57.15	40.66
44.45	44.45	60.33	41.48
47.63	47.63	63.50	41.48
50.80	50.80	66.68	42.26
53.98	53.98	69.85	42.26
57.15	57.15	73.03	43.86
60.33	60.33	76.20	43.86
63.50	63.50	82.55	44.65
66.68	66.68	85.73	45.44
69.85	69.85	88.90	45.44
73.03	73.03	93.65	47.83
76.20	76.20	96.82	47.83
79.38	79.38	101.60	47.83
82.55	82.55	104.78	47.83
85.73	85.73	107.95	47.83
88.90	88.90	111.13	47.83
92.08	92.08	114.30	47.83
95.25	95.25	117.48	47.83
98.43	98.43	120.65	47.83
101.60	101.60	123.83	47.83